

Material Safety Data Sheet



BLUESHIELD™ 6/ BLUESHIELD 7/ BLUESHIELD 8/
BLUESHIELD 21/ ALFLUX™

Section 1. Chemical product and company identification

Commercial name(s). : **BLUESHIELD™ 6/ BLUESHIELD 7/ BLUESHIELD 8/ BLUESHIELD 21/ ALFLUX™**
Material uses : Shielding gas for arc welding.
Supplier/Manufacturer : Air Liquide Canada Inc.
1250, René-Lévesque West, Suite 1700
Montreal, QC H3B 5E6
In case of emergency : (514) 878-1667

Section 2. Hazards identification

Physical state : Gas.
Emergency overview : WARNING!
HIGH PRESSURE GAS. GAS REDUCES OXYGEN AVAILABLE FOR BREATHING.
Keep away from heat (<52°C/125°F). Use only with adequate ventilation. Extremely hazardous gas under pressure. Keep cylinder valve closed when the product is not used.

Routes of entry : Inhalation. Dermal contact. Eye contact.
Potential acute health effects
Inhalation : Inhalation of this product may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation.
Skin : No known significant effects or critical hazards.
Eyes : No known significant effects or critical hazards.
Ingestion : Since the product is a gas, it will probably be inhaled rather than ingested. Consider first the preventive measures in case of inhalation.

Potential chronic health effects : Carcinogenic effects: Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.
Mutagenic effects: Not available.
Teratogenic effects: Not available.

Medical conditions aggravated by over-exposure : None known.

See toxicological information (section 11)

Section 3. Composition, Information on Ingredients

	CAS number	mole %
Canada		
Argon	7440-37-1	70 - 92
Carbon dioxide	124-38-9	8 - 30

This material is classified hazardous under the WHMIS Controlled Product Regulation in Canada.

See Sections 8, 11, 14 and 15 for details.

Section 4. First aid measures

Prompt medical attention is mandatory in all cases of overexposure to this non-flammable gaseous mixture. Rescue personnel should wear a self-contained breathing apparatus.

Inhalation : In case of inhalation, conscious persons should be assisted to an uncontaminated area and inhale fresh air. The person should be kept warmed and calm. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area, given assisted resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

- Skin contact** : In case of contact, immediately flush skin with plenty of water. Get medical attention if symptoms occur.
- Eye contact** : Individual in contact with a gas should not wear contact lenses. Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention if symptoms occur.
- Ingestion** : Since the product is a gas, it will probably be inhaled rather than ingested. Consider first the preventive measures in case of inhalation.
- Notes to physician** : The medical doctor must be warned that the person may suffer from anoxia.

Section 5. Fire fighting measures

- Flammability of the product** : Non-flammable.
- Products of combustion** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
- Fire hazards in the presence of various substances** : Container explosion may occur under fire conditions or when heated.
- Fire-fighting media and instructions** : Use an extinguishing agent suitable for the surrounding fire.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : EVACUATE ALL PERSONNEL FROM AFFECTED AREA.
Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. If leak is on container or container valve, contact the closest Air Liquide Canada location.
- Environmental precautions** : Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up** : Immediately contact emergency personnel. Stop leak if without risk. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

- Handling** : Valve protection caps must remain in place unless cylinder is secured with valve outlet piped to usage point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow to the cylinder. Do not tamper with (valve) safety device. Close valve after each use and when empty.
- Storage** : Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 52°C/125°F. Cylinders must be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in - first out" inventory system to prevent full cylinders being stored for excessive periods of time. Post "No Smoking or Open Flames" signs in the storage or use area. There should be no source of ignition in the storage or use area.

Section 8. Exposure controls/personal protection

Engineering controls : Use only in well-ventilated areas. Gas may accumulate in confined areas. Welding or brazing may produce fumes and gases that are hazardous to human health. Short-term (acute) overexposure to these products may cause discomforts, vertigo, nausea or dryness of the nose, mouth and eyes. Long-term (chronic) overexposure may affect the pulmonary function. Avoid breathing these gases and fumes.

Personal protection

Respiratory : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Wear suitable gloves for the application.

Eyes : Splash goggles.

Skin/Body : Wear appropriate personal protective suit.
Metal cap, safety shoes are recommended when handling cylinders.



Some applications of this product may require additional or other specific protective clothing. Please consult your supervisor.

Personal protection in case of a major leak : Safety glasses, goggles or face shield. Impervious gloves. Full suit. Metal cap, safety boots. Wear MSHA/NIOSH-approved self-contained breathing apparatus or equivalent and full protective gear.

Product name

Canada

Carbon dioxide

Exposure limits

CA Alberta Provincial (Canada, 10/2006).

15 min OEL: 54000 mg/m³ 15 minute(s).

8 hrs OEL: 5000 ppm 8 hour(s).

15 min OEL: 30000 ppm 15 minute(s).

8 hrs OEL: 9000 mg/m³ 8 hour(s).

CA British Columbia Provincial (Canada, 7/2007).

TWA: 5000 ppm 8 hour(s).

STEL: 15000 ppm 15 minute(s).

CA Ontario Provincial (Canada, 3/2007).

TWAEV: 5000 ppm 8 hour(s).

TWAEV: 9000 mg/m³ 8 hour(s).

STEV: 30000 ppm 15 minute(s).

STEV: 54000 mg/m³ 15 minute(s).

CA Quebec Provincial (Canada, 12/2006).

TWAEV: 5000 ppm 8 hour(s).

TWAEV: 9000 mg/m³ 8 hour(s).

STEV: 30000 ppm 15 minute(s).

STEV: 54000 mg/m³ 15 minute(s).

In Canadian provinces where no value is specifically suggested, the lowest value above should be used. Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Physical state : Gas.
Color : Colorless.
Odor : Odorless.
Solubility : Partially soluble in the following materials: cold water.

Section 10. Stability and reactivity

Stability and reactivity : The product is stable.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Acute Effects

Inhalation : Inhalation of this product may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation.
Skin : No known significant effects or critical hazards.
Eyes : No known significant effects or critical hazards.
Ingestion : Since the product is a gas, it will probably be inhaled rather than ingested. Consider first the preventive measures in case of inhalation.
Potential chronic health effects : Carcinogenic effects: Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.
 Mutagenic effects: Not available.
 Teratogenic effects: Not available.

Section 12. Ecological information




Products of degradation : These gases are released as is in the atmosphere.

Section 13. Disposal considerations

Disposal : Do not attempt to dispose of the container or of its content. Return in the shipping container properly labeled, with any valve outlet plugs or caps secured and valve protection cap in place to Air Liquide Canada for proper disposal. For emergency disposal, contact the closest Air Liquide Canada location.

Section 14. Transport information

NAERG : 115

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
TDG Classification	UN1956	COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)	2.2	-	
IMDG Class	UN1956	COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)	2.2	-	
IATA-DGR Class	UN1956	COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)	2.2	-	

PG* : Packing group

Additional information

Cylinders should be transported in a secure position, in a well ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards and should be discouraged.

Section 15. Regulatory information

Canada

WHMIS (Canada) : Class A: Compressed gas.



Canadian lists : **CEPA Toxic substances:** The following components are listed: Carbon dioxide
Canadian ARET: None of the components are listed.
Canadian NPRI: None of the components are listed.
Alberta Designated Substances: None of the components are listed.
Ontario Designated Substances: None of the components are listed.
Quebec Designated Substances: None of the components are listed.


Canada inventory (DSL/NDSL) : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	1
Fire hazard	0
Physical Hazard	0
Personal protection	G

National Fire Protection Association (U.S.A.)



HAZARD RATINGS

- 4- Extreme
- 3- Serious
- 2- Moderate
- 1- Slight
- 0- Minimal

See section 8 for more detailed information on personal protection.

References : ANSI Z400.5, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005. CGA C-7 Guide to the Preparation of Precautionary Labels and Marking of Compressed Gas Containers. CGA P-20 Standard for Classification of Toxic Gas Mixtures. CGA P-23 Standard for Categorizing Gas Mixtures Containing Flammable and Nonflammable Components.

Date of issue : 06/30/2008

Date of previous issue : 06/30/2005

Version : 4

Notice to reader

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROM SOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, AIR LIQUIDE CANADA INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.

Trademarks : **BLUESHIELD™** : Trademark of Air Liquide Canada Inc.
ALFLUX™ : Trademark of Air Liquide Canada Inc.